

IN THE SPECIFICATION

Please enter the following amendments to the specification, and the substitute specification (and Abstract) attached herewith. No new matter has been introduced.

TITLE

~~SOLID SOAP WITH CONNECTING AND~~ CONNECTED SOLID SOAPS WITH
KEEPING MEANS UNIT

TECHNICAL FIELD

BI The present invention relates to ~~solid soap with~~ a connecting and keeping unit for solid soap, which is capable of ~~being easily kept and used by~~ connecting with and utilizing several kinds of solid soap mutually different in ~~[[its]]~~ their usage~~[[;]]~~. ~~and more~~ More particularly, the invention relates to ~~solid soap with~~ a connecting and keeping unit, in which cleanser and perfume etc. can be ~~equipped together~~ kept with the solid soap and ~~[[a]]~~ loss of the solid soap can be prevented.

BACKGROUND ART

In ~~[[a]]~~ conventional use of solid soap, ~~[[it]]~~ the soap is ~~[[not]]~~ generally not dried, ~~specially in a~~ and this is especially true of the bottom part of the soap since the wet solid soap ~~wetted~~ is kept ~~in the~~ inside ~~[[of]]~~ a soap case. There is, therefore, a problem in that the solid soap ~~[[is]]~~ partially ~~crumbled~~ crumbles and is lost since the soap absorbs

moisture ~~in a part as it is~~ coming ~~[[in]]~~ into contact with the soap case. ~~[[thus]]~~ Thus, the surface of the soap is ~~gotten crumbled~~ crumbles. Furthermore, there is an inconvenience ~~[[of]]~~ in keeping and managing several kinds of solid soap.

DISCLOSURE OF THE INVENTION

Accordingly, the present invention is directed to ~~solid soap with~~ a connecting and keeping unit for solid soap that substantially ~~obviate~~ obviates one or more of the limitations and disadvantages of the related art.

B/c
could
A primary object of the present invention is to provide solid soap with a connecting and keeping unit, by means of which it is easy to keep ~~in custody~~ solid soap, and which selectively ~~[[use]]~~ contains several kinds of solid soap, ~~in a dry state of while~~ maintaining the solid soap ~~[[, and]]~~ in dry state. In addition, the soap is kept together ~~[[keep]]~~ with cleanser and perfume for use ~~[[of]]~~ in a bathroom ~~in custody~~.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects and features of the instant invention will become apparent from the following description of preferred embodiments taken in conjunction with the accompanying drawings, in which:

Fig. 1 is an ~~exemplified~~ exemplary perspective view ~~in accordance with~~ of one embodiment of the present invention;

Fig. 2 ~~[[shows]]~~ is an ~~exemplified~~ exemplary perspective view ~~[[for]]~~ of another

embodiment of the present invention;

Fig. 3 ~~depicts~~ is an ~~exampld~~ exemplary perspective view ~~for a still another~~ of a further embodiment of the present invention;

Fig. 4. is an ~~exampld~~ exemplary sectional view ~~for another~~ of an embodiment of a support body in accordance with the present invention; and

Fig. 5 ~~represents~~ is an ~~exampld~~ exemplary sectional view ~~for a still~~ of another embodiment of the support body ~~[[in]]~~ of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying ~~drawing~~ drawings.

B2 cont'd

In accordance with the present invention, Fig. 1 is a perspective view showing the construction of the invention as an example, and Figs. 2 and 3 are ~~exampld~~ exemplary perspective views ~~[[for]]~~ of another embodiment of a connecting unit, ~~[[and]]~~ while Fig. 4. ~~[[shows]]~~ is an ~~exampld~~ exemplary sectional view ~~[[for another]]~~ of an embodiment of a support body, and Fig. 5 ~~[[also]]~~ is an ~~exampld~~ exemplary sectional view ~~for a still~~ of another embodiment of the support body. As shown in the drawings, a support body 20 having a main portion 21 for supporting soap is partially buried ~~in the~~ inside ~~[[of]]~~ a soap body 10, and both end parts of the support body 20 are exposed outside the soap body ~~[[10c]]~~ 10 and are provided as a connecting unit 30 for connecting the soap thereto. As shown in Fig. 1, in the connecting unit 30, one end of the support body 20 has a ~~formation~~

of an insertion shaft 31a which is enlarged ~~from the~~ at an end part thereof, and another end of the support body 20 has a ~~formation of a~~ socket type clip 32a ~~[[whose]]~~ which has an expanded opening aperture ~~[[of]]~~ at an end part thereof. ~~is expanded, thereby~~ As a result, several cakes of soap can be connected with one another consecutively. In Fig. 2, indicating which is an ~~exampled~~ exemplary diagram ~~[[for]]~~ of another connecting unit ~~[[30]]~~ 30b, one end of the support body 20 has a ~~formation of a~~ hook part 31b and another end thereof has a ~~formation of a~~ ring type insertion part 32b ~~[[on]]~~ into which the hook part 31b may be inserted and hooked, so as to thereby ~~[[gain]]~~ provide a connection ~~[[of]]~~ for the soap. In Fig. 3, which is ~~representing~~ an ~~exampled~~ exemplary diagram ~~for a still~~ of another connecting unit ~~[[30]]~~ 30c, one end of the support body 20 has a ~~formation of a~~ bolt part 31c and ~~[[its]]~~ another end has a ~~formation of a~~ nut part 32c, so as to ~~then obtain~~ provide a connection ~~[[of]]~~ for several cakes of soap. In Fig. 4, which is ~~illustrating~~ an ~~exampled~~ exemplary diagram ~~[[for]]~~ of the support body 20, there is formed ~~in its portion~~ a receptacle 40 ~~[[whose]]~~ having one side ~~[[in]]~~ of the connecting unit 30 ~~[[is]]~~ provided as a stopper 41 to open and close the receptacle 40, the receptacle 40 being ~~[[put]]~~ provided with cleanser or perfume which can be ~~equipped together~~ used with the soap. The stopper 41 of the receptacle 40 is formed in the support body 20 and is enlarged as shown in Fig. 5, so that the ~~[[a]]~~ connecting unit 30 ~~[[as]]~~ can be used as a sitting support die 33 ~~can be also formed and used.~~

Bl
cat'd

INDUSTRIAL APPLICABILITY

As ~~afore-mentioned~~ previously mentioned, in accordance with the present invention, the soap body 10 is supported by the support body 20 and the connecting unit 30, 30b or 30c is provided at ~~[[in]]~~ both ends of the support body 20. ~~Accordingly, is also provided therein, accordingly~~ a user can selectively use desired soap ~~[[under]]~~ chosen from a consecutive connection ~~[[state]]~~ of ~~[[the]]~~ several bars of solid soap. There is also a convenience ~~to use one~~ in that a cake of solid soap can be mounted or displayed together with ~~another~~ perfume or cleanser or other necessities for use ~~[[of]]~~ in a bathroom ~~[[by]]~~ as a result of provision of the inventive receptacle formed in the support body 20. In addition, crumbling and loss of the soap can be prevented ~~from being crumbled and lost~~ by ~~[[using]]~~ use of the hook 50 or the sitting support die 33.

Although the invention has been shown and described with respect to the preferred embodiments, it will be understood by those skilled in the art that various changes and modifications may be made without departing from the spirit and scope of the invention as defined in the following claims.